

10500949

10/500949

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

Rec'd PCT/PTO

07 JUL 2004

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
7 August 2003 (07.08.2003)

PCT

(10) International Publication Number
WO 03/064541 A1(51) International Patent Classification⁷: **C09B 67/04**,
67/10, 67/22(74) Common Representative: **CIBA SPECIALITY
CHEMICALS HOLDING INC.**, Klybeckstrasse 141,
CH-4057 Basel (CH).(21) International Application Number: **PCT/EP03/00647**

(22) International Filing Date: 23 January 2003 (23.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PCT/EP02/01018 31 January 2002 (31.01.2002) EP
02405666.5 31 July 2002 (31.07.2002) EP(71) Applicant (for all designated States except US): **CIBA
SPECIALITY CHEMICALS HOLDING INC.**
[CH/CH]; Klybeckstrasse 141, CH-4057 Basel (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BUGNON, Philippe**
[CH/CH]; Impasse des Rosiers 4, CH-1724 Essert (CH).
MAURER, Marc [FR/FR]; Rue de la Pyramide 8, F-68128
Village-Neuf (FR).(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: MANUFACTURING AND CONDITIONING OF SOLID SOLUTION ORGANIC PIGMENTS

(57) Abstract: Organic solid solution pigments are prepared and conditioned by treating a mixture of their components, after syn-
thesis but preferably without or with only partial drying, in a mixture of from 0 to 30% by weight of an organic liquid having a
dipole moment μ of $2.8 - 6.0 \cdot 10^{-18}$ esu (2.8 to 6.0 debye units) and from 70 to 100% by weight of water in an agitated media pearl
mill having a specific power density of at most $2.0 \text{ kJ} \cdot \text{s}^{-1}$ per litre of grinding space. Drying the starting components is especially
suitable in the case of only slightly agglomerating, easy to wet pigments of specific surface area from 1 to $25 \text{ m}^2/\text{g}$. The method
gives excellent results, and is flexible and also much simpler than known methods.

WO 03/064541 A1